

DUMBWAITER SALES THE SMART WAY TO BUY A DUMBWAITER



Dumbwaiter Model: P-300 MJ-500

Have you contacted your local code enforcement for safety requirements?	Yes <input type="checkbox"/>	No <input type="checkbox"/>
Is the dumbwaiter going to be installed in a residence?	Yes <input type="checkbox"/>	No <input type="checkbox"/>
Is there living space below the dumbwaiter shaft?	Yes <input type="checkbox"/>	No <input type="checkbox"/>
What will the dumbwaiter primarily be used for?	_____	
How many times will the dumbwaiter be used?	_____ per	Hour _____

Job Name: _____

Contractor's Name, Phone #, & Email: _____

Ship to address: _____

Is the "Ship To" address a commercial location? Yes No

Installation address: _____

Owners' Name & Phone # _____

Owners' information is for warranty records only. Powerlift does not contact the owner. Powerlift does not install or service dumbwaiters.

1. The finished floor to finished floor measurements:
 Bottom floor to middle floor: _____ Middle floor to top floor: _____

2. The overall height of shaft: _____
 (The distance from the bottom floor to the ceiling of the top floor.)

3. The **finished** shaft width and depth: (The distance from the **finished** wall surface to **finished** wall surface.)
 Shaft Width: _____ Shaft Depth: _____

4. Desired loading heights: (Usually 36", this is the height above the floor where the dumbwaiter car will stop.)
 Bottom floor: _____ Middle floor: _____ Top floor: _____


5. Use the diagram on the right to mark the locations of your openings and mark one wall to mount the rail assembly to.

- Rails
- Opening at top floor
- Opening at middle floor

****For clarity, stand on the bottom floor and face the "Bottom Floor Opening" to properly mark the locations on the diagram.****

6. While facing each opening which side will the door handle be on? **Left or Right**
 Bottom floor: _____
 Middle floor: _____ Top floor: _____

- Rails
- Opening at top floor
- Opening at middle floor



- Rails
- Opening at top floor
- Opening at middle floor

****Bottom Floor Opening****

- Opening at top floor
- Opening at middle floor

7. Desired voltage for dumbwaiter:
 Single Phase - 208 V 230 V (extra for MJ-500)
 Three Phase - 208 V 230 V 460 V

8. Dumbwaiter cars come with a 3" Lip. No Lip requires a car gate. 3" LIP NO LIP

9. Accessories / Special Instructions: _____

DUMBWAITER ~ THE SMART WAY TO BUY A DUMBWAITER ~ THE SMART